



C5051/C5045 C5035/C5030

Product Specifications

OFFICE SOLUTIONS







Finisher-C1



External 2/3-Hole



with Inner Finisher Additional Tray-A1



imageRUNNER ADVANCE

Cassette Feeding Unit-AD1



Cabinet Type-B



Paper Deck Unit-B1

Main Unit

System Type

Color Digital Multifunction Imaging System

Functions

Standard: Copy, Print (UFR II), Scan,

Send, Store

Print (PCL, Adobe® PostScript® 3™), Optional:

Fax (Up to 4 Lines)

Operation Panel

8.4" SVGA Full-color, TFT Screen

Memory

2GB RAM Standard: 2.5GB RAM Maximum:

Hard Disk Drive

Standard: Maximum: 250GB

Mirroring Hard Disk Drive

Optional (80GB, 250GB) Method: RAID1

Network Interface Connection

Standard: 10/100/1000Base-TX Wireless LAN (IEEE 802.1x) Optional:

Other Interface

Standard: USB 2.0 (Host)x2, USB 2.0 (Device)

Optional: Device Port [USB 2.0 (Host)x2], Serial Interface, Copy Control

Interface

Copy/Print Speed (BW/Color)

C5051: Up to 51/51 ppm C5045: Up to 45/45 ppm C5035: Up to 35/35 ppm C5030: Up to 30/30 ppm

Legal/11" x 17": C5051/C5045: Up to 26/26 ppm

C5035/C5030: Up to 18/18 ppm

Paper Sources (20 lb. Bond)

Standard: Dual 550-sheet Cassettes 100-sheet Stack Bypass

Dual 550-sheet Cassettes

Optional: 2,700-sheet Paper Deck

5.000 Sheets Maximum:

Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (Inner Tray)

3.100 Sheets (with Staple Finisher Maximum:

or Booklet Finisher)

Output Paper Sizes

Cassettes: 12" x 18",* 11" x 17",* Legal, Letter,

Letter-R, Statement-R, Executive, Custom Size [5-1/2" x 7-1/8" to 12" x 18" (139.7mm x 182mm to

305mm x 457mm)]

12" x 18", 11" x 17", Legal, Letter, Bypass:

Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18

(99mm x 140mm to 320mm x

457mm) Letter Paper Deck:

Envelope Feeder Attachment* Other Ontions: (COM10 No.10, Monarch, DL, ISO-B5,

ISO-C5) Tab Feeding Attachment Kit**

Acceptable Paper Weights

14 lb. Bond to 110 lb. Index Cassettes:

(52 to 209g/m²)

14 lb. Bond to 140 lb. Index Bypass:

(52 to 256a/m²)

Duplexing

Paper Size: Standard Automatic Trayless Duplexing (Executive to 12" x 18")

Paper Weights: 14 lb. Bond to 110 lb. Index

(52 to 209g/m²)

Special Media Support

Tracing, Labels, Transparency, Tab, and Envelopes

Warm-up Time

38 Seconds from Power On

C5051/C5045 18 Seconds from Sleep Mode C5035/C5030: 15 Seconds from Sleep Mode

Power Requirements/Plug

C5051/C5045: 120V AC, 60Hz, 20A/NEMA 5-20P C5035/C5030: 120V AC, 60Hz, 15A/NEMA 5-15P

Power Consumption

C5051/C5045: Maximum: 1,800W; Sleep Mode: 1W C5035/C5030: Maximum: 1,300W; Sleep Mode: 1W

Dimensions (H x W x D)

38-5/8" x 24-3/8" x 29-7/8" C5051/C5045: (982mm x 620mm x 760mm)

37" x 24-3/8" x 29" C5035/C5030: (938mm x 620mm x 735mm)

Installation Space (W x D) C5051/C5045: 42-1/8" x 52"

(1071mm x 1319mm) C5035/C5030: 42-1/8" x 49-5/8" (1071mm x 1259mm)

Weight

C5051/C5045: Approx. 379 lb. (172kg)*** C5035/C5030: Approx. 342 lb. (155kg)***

Toner (Estimated Toner Yield @ 5% Coverage) C5051/C5045: Black: 44,000 Images

Color (C,M,Y): 38,000 Images 36,000 Images C5035/C5030: Black:

Color (C,M,Y): 27,000 Images





C5051/C5045 C5035/C5030

Main Unit (continued)

Image Reader Unit

Scan Resolution

Up to 600 x 600 dpi

Acceptable Originals

Sheet, Book, 3-Dimensional Objects [up to 4.4 lb. (2kg)]

Maximum Original Size

Up to 11" x 17'

Document Feeder

Scan Method

C5051/C5045

Single-pass Duplexing Automatic Document Feeder

C5035/C5030

Duplex Automatic Document Feeder

Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R,

Statement, or Statement-R

Paper Weights: One-sided Scanning: 11 lb. Bond to 32 lb. Bond (42 to 128g/m²)

Two-sided Scanning: 13 lb. Bond to 32 lb. Bond (50 to 128g/m²)

Scan Speed (BW/Color: Letter)

C5051/C5045

Simplex: Up to 70/70 ipm (300 dpi)

Up to 70/51 ipm (600 dpi)

Up to 100/100 ipm (300 dpi) Duplex

Up to 70/51 ipm (600 dpi)

C5035/C5030

Up to 46/46 ipm (300 dpi) Simplex:

Up to 46/46 ipm (600 dpi)

Up to 17.5/17.5 ipm (300 dpi) Duplex: Up to 17.5/17.5 ipm (600 dpi)

Paper Capacity (20 lb. Bond)

C5051/C5045 150 Sheets

C5035/C5030 100 Sheets

Copy Specifications

First-Copy-Out Time (Letter)

C5051/C5045

RW. 4.0 Seconds

6.5 Seconds

C5035/C5030

BW: 5.5 Seconds

Color: 8.9 Seconds

Multiple Copies 1 to 999

Color Mode

Auto Color, Full Color, Black, Single Color, Two Colors

Copy Exposure

Automatic or Manual (9 levels)

Magnification

25% - 400% (1% increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-sided, Exposure Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Booklet, Transparency Interleaving, Shift, Margin, Frame Erase Image Combination, Different-size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/Positive Inversion, Image Repeat, Mirror Image, Sharpness, Tab Paper Creation, Form Composition, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date, Job Block Combination, Store in User Inbox

Print Specifications

Processor

Canon Dual Custom Processor (Shared)

Memory

Standard:

2GB RAM

Maximum: 2.5GB RAM

Hard Disk Drive

Standard: 80GB

250GB Maximum:

Maximum Engine Resolution 1200 x 1200 dpi

PDL Support

Standard:

Optional: PCL 5c, PCL 6, Adobe PS 3

Print Driver Supported OS

UFR II: Windows® (Windows 2000/

XP/Server 2003/Server 2008/ Windows Vista®, Windows 7), Citrix MetaFrame, Macintosh® (OS X 10.4.9

or later)

Windows (Windows 2000/ PCL 5c/6:

XP/Server 2003/Server 2008/ Windows Vista, Windows 7), Citrix

Windows (Windows 2000) Adobe PS 3:

XP/Server 2003/Server 2008/ Windows Vista, Windows 7), Citrix MetaFrame, Macintosh (OS X 10.4.9

XPS: Windows Vista, Windows Server

2008, Windows 7

Direct Print Support

Standard: TIFF, JPEG, EPS[†]

PDF, XPS Optional:

Print Features

Suspend Job Timeout, Feature, Subset Finishing (PS only), Profile Settings, Secure Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Booklet Printing, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Black-and-White Printing, Objective, Color/Black-and-White Auto Detect, Toner Reduction, Poster Printing, PANTONE® named Color Profiles

Scan Specifications

Network TWAIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Universal Send Specifications

Sending Method

E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), User Inbox, Super G3 Fax (Optional)

Color Mode

Auto Color Select (Full Color, Grayscale), Auto Color Select (Full Color, B/W), Full Color, Grayscale, B/W

600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi. 200 x 400 dpi, 400 x 400 dpi, 300 x 300 dpi 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100 dpi

Address Book Capacity

Max. 1,800 Destinations (incl. 200 One-Touch Buttons)

Communication Protocol

FTP (TCP/IP), SMB (TCP/IP), File:

WebDAV

E-mail/I-Fax: SMTP. POP3. I-Fax (Simple. Full)

File Format

TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimize for Standard:

Web), PDF/A-1b, XPS, XPS (Compact)

PDF (Trace & Smooth), PDF/XPS Optional:

(OCR), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions), Office Open XML (OCR)

I-Fax Data Format

B/W TIFF (MH, MR, MMR)

Color: TIFF (Profile-C)

Fax Specifications

Maximum Number of Connection Lines

Modem Speed

Super G3: 33.6 Kbps 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi,

200 x 100 dpi

Sending/Recording Size

Statement to 11" x 17'

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type, Two-sided Original, Book to Two Pages





C5051 / C5045 C5035 / C5030

Main Unit (continued)

Store Specifications		
Mail Box		
No. Supported:	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes	
Max. Pages Stored:	6,000	
Advanced Box		
Available Disk Space:	Approx. 10GB (Standard HDD) 113GB (250GB HDD)	
Communication Protocol:	SMB or WebDAV	
Supported Client PC:	Windows (Windows 2000/XP/ Windows Vista)	
Max. Number of Concurrent Connection:	SMB: 32, WebDAV: 12 (Active Sessions)	
Advanced Box Features:	Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support	
Memory Media		
Standard:	USB Memory	
Optional:	SD, SDHC, CompactFlash, Memory Stick, Microdrive	

Security Specifications

Standard

Department ID Management, Single Sign-On H, Access Management System (Device and Function Level Log-in), Secured Print, Trusted Platform Module, User Access Control of Advanced Box, Mail Box Password Protection, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPvI/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, Adobe® LiveCycle® Rights Management ES2 Integration

Optional

Removable HDD, HDD Erase, HDD Encryption/Mirroring, Encrypted Secure Print, Encrypted PDF, Document Scan Lock, IPSec, Secure Watermark, IEEE2600.1 Common Criteria Certification ••

Environmental Information

ENERGY STAR® Qualified, RoHS Compliant, Ecomark, Blue Angel, WEEE Directive

Optional Accessories

Paper Supply O		
Cassette Feeding Unit-AD1		
Paper Capacity:	550 Sheets x 2 Cassettes (20 lb. Bond)	
Acceptable Paper Weight:	14 lb. Bond to 110 lb. Index (52 to 209g/m²)	
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, and Custom Size [5-1/2" x 7-3/16' to 12" x 18" (139.7mm x 182mm to 305mm x 457mm)]	
Power Source:	From Main Unit/Approx. 30W	
Maximum Power Consumption:	Approx. 30W	
Dimensions (H x W x D):	9-7/8" x 24-3/8" x 27-5/8" (251mm x 620mm x 700mm)	
Weight:	Approx. 60.6 lb. (27.5kg)	
Paper Deck Unit-B	1++	
Paper Capacity:	2,700 Sheets (20 lb. Bond)	
Acceptable Paper Weight:	14 lb. Bond to 28 lb. Bond (52 to 105g/m²)	
Acceptable Paper Size:	Letter	
Power Source/ Maximum Power Consumption:	From Main Unit/Approx. 45W	
Dimensions (H x W x D):	18-5/8" x 14-5/8" x 23-3/4" (473mm x 372mm x 603mm)	
Weight:	Approx. 81.6 lb. (37kg)	
Envelope Feeder A	attachment-D1**	
Paper Capacity:	50 Sheets (or 30mm in height)	
Acceptable Envelope Sizes:	COM10 No.10, Monarch, DL, ISO-B5, ISO-C5	
Feeding Speed:	10 cpm	
Dimensions (H x W x D):	3-1/4" x 17-1/4" x 12-1/8" (81mm x 439mm x 307mm)	
	Approx. 2.6 lb. (1.2kg)	
Weight:		
Weight: Copy Tray-J1*** Total Output Capacity:	100 Sheets (20 lb. Bond)	
Copy Tray-J1*** Total Output	100 Sheets (20 lb. Bond) 14 lb. Bond to 110 lb. Index (52 to 209g/m²)	
Copy Tray-J1*** Total Output Capacity: Acceptable	14 lb. Bond to 110 lb. Index	
Copy Tray-J1*** Total Output Capacity: Acceptable Paper Weight: Acceptable	14 lb. Bond to 110 lb. Index (52 to 209g/m²) 11" x 17", Legal, Letter, Letter-R,	

Output Options

Output Options Inner 2-Way Tray-F1				
Total Output Capacity:		neets (20 lb. Bond) Sheets (20 lb. Bond)		
Acceptable Paper Weight:	14 lb. Bond to 14 (52 to 256g/m²)	0 lb. Index		
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-1/2" to 12-5/8" x 18" (99mm x 140mm to 320mm x 457mm)] and Envelopes			
Dimensions (H x W x D):	3" x 16-3/4" x 16 (76mm x 426mn			
Weight:	Approx. 1.3 lb. (5	i74g)		
Inner Finisher-A1				
Number of Trays:	Additional Tray-	rith Inner Finisher A1)		
Total Output Capacity:	Without Inner Finisher Additional Tray-A1:	500 Sheets		
	With Inner Finisher Additional Tray-A1:	Top Tray: 100 Sheets (Letter) Lower Tray: 200 Sheets (Letter)		
Acceptable Paper Weight:	14 lb. Bond to 140 lb. Index (52 to 256g/m²)			
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size [3-7/8" x 5-9/16" to 12-5/8" x 18" (99mm x 140mm to 320mm x 457mm)] and Envelopes			
Staple Positions:	Corner Stapling: Letter, Letter-R	11" x 17", Legal,		
	Double Stapling: Letter, Letter-R	11" x 17", Legal,		
Max. Stapling Capacity:	30 Sheets (22 lb.	Bond - 21 lb. Bond) Bond - 28 lb. Bond) Bond - 140 lb. Index)		
	20 Sheets (22 lb	etter-R: Bond - 21 lb. Bond) . Bond - 28 lb. Bond) Bond - 140 lb. Index)		
Paper Capacity of Staple Mode:	Top Tray: 3/8" in Height Lower Tray: 30 Sets (or 2-1/2" in Height)			
Type of Staple:	Staple-J1 (5,000	x 3)		
Power Source/ Max. Power	- M: 11:17			
Consumption:	From Main Unit/			
Dimensions (H x W x D):	9-1/4" x 34-1/8" (234mm x 865m (when Auxiliary			
Weight:	Approx. 28.7 lb. (when Inner Finis Tray-A1 is attach	sher Additional		





C5051 / C5045 C5035 / C5030

Optional Accessories (continued)

Staple Finisher-C1	
Number of Trays:	2
Total Output Capacity:	3,000 Sheets (Letter, Statement-R, Executive)
	Top Tray: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)
	Lower Tray: 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R)
Acceptable Paper Weight:	14 lb. Bond to 140 lb. Index (52 to 256g/m²)
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, ** Statement-R, Executive, and Envelopes
Staple Positions:	Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive
	Double Stapling: 11"x 17", Legal, Letter, Letter-R, Executive
Max. Stapling Capacity	Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond) 30 Sheets (22 lb. Bond to 28 lb. Bond) 2 Sheets (29 lb. Bond to 140 lb. Index)
	11" x 17", Legal, Letter-R: 30 Sheets (14 lb. Bond to 21 lb. Bond) 20 Sheets (22 lb. Bond to 28 lb. Bond) 2 Sheets (29 lb. Bond to 140 lb. Index)
Paper Capacity of Staple Mode:	Top Tray: 1,300 Sheets/30 Sets (Letter, Executive) 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)
	Lower Tray: 1,700 Sheets/30 Sets (Letter, Executive) 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)
Type of Staple:	Staple-J1 (5,000 x 3)
Power Source/ Max. Power Consumption:	From Main Unit/Approx. 117W (when External 2/3-Hole Puncher-B1 is attached)
Dimensions (H x W x D):	43-1/4" x 26-5/8" x 25-1/2" (1097mm x 677mm x 646mm) (when Auxiliary Tray is extended)
Weight:	Approx. 101 lb. (46kg)

3,000 Sheets (Letter, Statement-R, Executive) Top Tray: 1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) 14 lb. Bond to 140 lb. Index (52 to 256g/m²) 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, and Envelopes Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond' 30 Sheets (14 lb. Bond to 28 lb. Bond' 30 Sheets (22 lb. Bond' 50 Sheets (22 lb. Bond' 50 Sheets (14 lb. Bond to 28 lb. Bond' 50 Sheets (22 lb. Bond' 50 Sheet
1,300 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) Lower Tray: 1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) 14 lb. Bond to 140 lb. Index (52 to 256g/m²) 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-A Statement-R, Executive, and Envelopes Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond
1,700 Sheets (Letter, Statement-R, Executive) 650 Sheets (11" x 17", Legal, Letter-R) 14 lb. Bond to 140 lb. Index (52 to 256g/m²) 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, ♣▲ Statement-R, Executive, and Envelopes Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
(52 to 256g/m²) 12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, ♣ Statement-R, Executive, and Envelopes Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
Letter-R, Statement, A Statement-R, Executive, and Envelopes Corner Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
11" x 17", Legal, Letter, Letter-R, Executive Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
Double Stapling: 11" x 17", Legal, Letter, Letter-R, Executive Saddle-stitch: 12" x 18", 11" x 17", Legal, Letter-R Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
Letter, Executive: 50 Sheets (14 lb. Bond to 21 lb. Bond)
50 Sheets (14 lb. Bond to 21 lb. Bond
2 Sheets (29 lb. Bond to 140 lb. Index)
11" x 17", Legal, Letter: 30 Sheets (14 lb. Bond to 21 lb. Bond 20 Sheets (22 lb. Bond to 28 lb. Bond 2 Sheets (29 lb. Bond to 140 lb. Index;
Top Tray: 1,300 Sheets/30 Sets (Letter, Executive) 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)
Lower Tray: 1,700 Sheets/30 Sets (Letter, Executive) 650 Sheets/30 Sets (11" x 17", Legal, Letter-R)
16 Sheets (14 lb. Bond to 20 lb. Bond (12" x 18", 11" x 17", Legal, Letter-R)
10 Sheets (22 lb. Bond to 28 lb. Bond (12" x 18", 11" x 17", Legal, Letter-R)
25 Booklets (5-sheet Booklets)
Staple Cartridge-D2 (2,000 x 3)
From Main Unit/Approx. 117W (when External 2/3-Hole Puncher-B1 is attached)
From Main Unit/Approx. 117W (when External 2/3-Hole Puncher-B1

	14 lb. Bond to 140 lb. Index
Paper Weight:	(52 to 256g/m²)
Acceptable Punch Paper Size:	11" x 17", Legal, Letter, Letter-R
Punch Type:	2 Holes (Legal, Letter-R)
	3 Holes (Letter, 11" x 17")
Distance between Punch Holes:	2 Holes: 2-3/4" (70mm)
	3 Holes: 4-1/4" (108mm)
Punch Waste Tray Capacity:	Approx. 2,500 Sheets (20 lb. Bond)
Power Source:	From Main Unit
Dimensions (H x W x D):	35-3/4" x 4-1/4" x 24-1/2" (908mm x 107mm x 623mm)
Weight:	Approx. 15.9 lb. (7.2kg)
Print Controller	Options
imagePASS-B1■	
Туре	Embedded
Connectable Devices:	imageRUNNER ADVANCE C5051/ C5045/C5035/C5030
Processor:	Intel® Celeron® M440 1.88GHz
System:	System 8e Release2
Memory:	Standard: 512MB Maximum: 1GB
Hard Disk:	80GB
DVD-ROM:	N/A
Interface Connections:	10/100/1000Base-T (RJ-45)
PDL Support:	Adobe PS 3/PCL 5c/PCL 6
Print Resolution:	1200 x 1200 dpi 2400 dpi Equivalent x 600 dpi
Print Driver Supported OS:	Adobe PS 3: Windows (Windows 2000/XP/Server 2003/Server 2008, Windows Vista), Macintosh (OS X 10.3.9 or later)
	PCL 5c/6: Windows (Windows 2000/ XP/Server 2003/Windows Vista)
Utility Software:	Remote Scan 5.3, Command WorkStation® for Windows, Command WorkStation for Mac, Web Tools
Standard Features:	Auto Trapping, Paper Catalog
EFI Options:	Hot Folder v2.0, Secure Erase V1.1, SeeQuence Suite, SeeQuence Impose, SeeQuence Compose, 512Mi Optional Memory, X-Rite Eye-One





C5051 / C5045 C5035 / C5030

Optional Accessories (continued)

ColorPASS-GX300■		
Type:	External	
Connectable Devices:	imageRUNNER ADVANCE C5051	
Processor:	Intel® Core™2 Duo, Xeon E8400 2 x 3.0GHz FSB 1333MHz	
System:	System 9 Release2	
Memory:	Standard: 2GB Maximum: 2GB	
Hard Disk:	160GB	
DVD-ROM:	Standard (DVD-RW)	
Interface Connections:	10/100/1000Base-T (RJ-45)	
PDL Support:	Adobe PS 3	
Print Driver Supported OS:	Windows (Windows 2000/XP/ Server 2003/Server 2008/Windows Vista), Macintosh (OS X 10.3.9 or later)	
Print Resolution:	1200 x 1200 dpi, 2400 dpi Equivalent x 600 dpi	
Utility Software:	Remote Scan 5.3, Command WorkStation® for Windows, Command WorkStation for Mac, WebTools	
Standard Features:	Auto Trapping, Paper Catalog, Hot Folders, Virtual Printers, Secure Erase	
EFI Options:	Integrated Interface and Stand, X-Rite Eye-One, SeeQuence Suite, SeeQuence Impose, SeeQuence Compose, Removable Hard Disk Drive Kit, Graphic Arts Feature Set Premium v2.2	
Dimensions (H x W x D):	19-1/8" x 8-1/2" x 19-1/8"	
Weight:	Approx. 43.5 lb.	

Other Optional Accessories

Cabinet Type-B Inner Finisher Additional Tray-A1 Tab Feeding Attachment Kit-B1** Utility Tray-A1 USB Keyboard Key Switch Unit-A2 Card Reader-C1 Copy Card Reader Attachment Kit-B1 Braille Label Kit ADF Access Handle-A1 Stamp Ink CRG-C1 Stamp Unit-B1 imageRUNNER ADVANCE Essentials Universal Send Advanced Feature Set-D1 Universal Send Security Feature Set-D1 Universal Send Digital User Signature Kit-C1 Super G3 Fax Board-AE1 Super G3 2nd Line Fax Board-AE1® Super G3 3rd/4th Line Fax Board-AE1 ** Remote Fax Kit-A1 *** PS Printer Kit-AE1■ PCL Printer Kit-AE1 Direct Print Kit (for PDF/XPS)-H1 Encrypted Secure Print-D1 Barcode Printing Kit-D1* Web Access Software-H1** Secure Watermark-B1 Wireless LAN Board-B1 *** USB Device Port-B1 Multimedia Reader/Writer-A1⁺ Additional Memory Type B (512MB) Document Scan Lock Kit-A1 Data Erase Kit-C1 HDD Data Encryption and Mirroring Kit-C1 Removable HDD Kit-AC1 2.5-inch/80GB HDD-C1** 2.5-inch/250GB HDD-D1 IPSec Board-B2*** Expansion Bus-F1 Voice Guidance Kit-F1*** Voice Operation Kit-C1*** Remote Operator's Software Kit-B1 Copy Control Interface Kit-A1° eCopy Suite imageWARF Suite iR-ADV Security Kit-A1 for IEEE2600.1 Common Criteria Certificationoc

- * Not available in top cassette.
- ** Installs on Cassette 2. Cannot install Envelope Feeder
 Attachment and Tab Feeding Attachment Kit at same time.
- *** Includes consumables.
- ^A Requires the Canon PS Printer Kit-AE1.
- $^{\dagger}\,\mbox{EPS}$ and XPS cannot be printed directly from Memory Media or Advanced Box.
- ^{††} Cannot be installed with Cabinet Type-B.
- +++ Cannot be installed with Booklet Finisher-C1 or Staple Finisher-C1.
- Cannot be installed with Booklet Finisher-C1, Staple Finisher-C1, or Inner Finisher-A1.
- ▲▲ Statement cannot be used when the External 2/3-Hole Puncher-B1 is attached.
- ▲▲▲ External 2/3-Hole Puncher-B1 can only be installed with either the Staple Finisher-C1 or Booklet Finisher-C1.
- Requires Additional Memory Type B (512MB).
- Cannot be installed when Cassette Feeding Unit-AD1 is installed.
- Requires Copy Card Reader Attachment Kit-B1.
- Requires Super G3 Fax Board-AE1.
- •• Requires Super G3 Fax Board-AE1 and Super G3 2nd Line Fax Board-AE1.
- ••• Cannot be installed with Super G3 Fax Board-AE1.
- * Requires PCL Printer Kit-AE1.
- ** Requires PS Printer Kit-AE1 or Direct Printer Kit (for PDF/XPS)-H1 for printing PDF files.
- *** Requires Expansion Bus-F1.
- * Requires Device Port-B1.
- ** 80GB HDD for Mirroring functionality only, cannot be used to increase storage.
- *** Voice Operation Kit-C1 and Voice Guidance Kit-F1 cannot be installed together.
 - Cannot be installed with Serial Interface Kit-K1 or Card Reader-C1
- O Specified configurations and settings need to be applied to the device in order to achieve and maintain IEEE2600.1 Common Criteria Certification. Contact your Canon Authorized Dealer for more information.

NOTE: Some accessories require additional equipment or may be prerequisites for other options. Some accessories cannot be installed simultaneously. Check with your Canon Authorized Dealer for details.



1-800-OK-CANON www.usa.canon.com

Canon U.S.A., Inc. One Canon Park Melville, NY 11747

ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. PANTONE and other Pantone, LLC trademarks are the property of Pantone, LLC. CANON, IMAGERUNNER, IMAGEPASS, COLORPASS, MEAP, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meets the

©2013 Canon U.S.A., Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.













